

[www.schnellputz.com](http://www.schnellputz.com)

# SCHNELL PUTZ



- ◆ Bonding Coats
- ◆ Cement Renders/Plasters
- ◆ Decorative Colour Renders
- ◆ Decorative Texture Finishes
- ◆ Gypsum Plasters
- ◆ Masonry Mortars

- ◆ Tile Adhesives
- ◆ Tile Grouts
- ◆ Floor Screeds
- ◆ Repair Mortars
- ◆ Non-shrink Grouts
- ◆ Insulation Mortars

# Company Profile

# SCHNELL PUTZ

“Schnell Putz” is a leading brand name for premium quality Dry mix products.

We offer premium high-quality products, advanced know-how, timely technical assistance and unlimited customer service.

Schnell Putz is able to meet most challenging product requirements to provide effective solutions to the construction market and building industry. We achieve customer satisfaction through quality management, high technical expertise and quality services on a wide range of Dry mix products. The advanced state-of-the-art Schnell Putz automated plant ensures a continuous control over the production process assuring constant quality of the products offered.

Schnell Putz offers a wide range of machines for the mixing and application of the products providing customers savings in time & work force. The automated mixing machines assure continuous quality control in the application process.

## Quality

Schnell Putz quality standards are ISO 9001:2015 certified. Raw materials and finished products are subjected to strict quality control checks by the QC department ensuring confirmation with international product specifications as per BS EN/ASTM standards. Schnell Putz In-house technical lab is equipped with all equipments required for the testing of raw materials and finished plaster products.

## Support

In construction industry the technical support plays an important role. Schnell Putz offers experienced and dedicated on time technical team to support our customers. The premium quality of the products and technical services ensure the total customer satisfaction to meet most challenging expectations.

Schnell Putz support is distinct by the continuous development producing high quality Dry mix products and technical services with more than a decade of experience in the region.

## Eco-friendly

Schnell Putz is an Eco-friendly company dedicated towards a clean work environment and LEED products. The company is committed to produce eco-friendly LEED complied products by harvesting regional raw materials and dust free manufacturing/application process. We offer clean and healthy job site adding more value to HSE.

## Advantages

- | Premium quality
- | Regional product design & development
- | Wide product range
- | Prompt service & delivery
- | Quick response technical team
- | Specialized
- | Saves time and man power
- | Consistent quality throughout the project
- | Dry mix products require only the addition of water at site
- | Clean and healthy job site adding value to HSE
- | Most modern machines and tools for the application

## Product range

- | Bonding Coats
- | Cement Plaster/Renders
- | Gypsum Plasters
- | Special Plasters
- | Masonry Mortars
- | Tile Adhesives
- | Floor Screeds
- | Repair Mortars
- | Non-shrink Grouts
- | Insulation Mortars





## Product list

Product category/name/code		Field of application	Packing	Approx. coverage [per tonne]
Bonding Rush Coats	<b>Bonding Coat SP10</b>	Bonding coat for rendering on normal fair faced concrete surfaces. Application by tyrolean box/ spray gun @ 2-5mm.	50 kg bags	430 m <sup>2</sup> @ 2mm thickness
	<b>Bonding Coat SP12</b>	Bonding coat for rendering on densified concrete surfaces. Application by tyrolean box/ spray gun @ 2-5mm.	50 kg bags	430 m <sup>2</sup> @ 2mm thickness
	<b>Bonding Coat SP14</b>	Bonding coat for rendering on ultra smooth concrete surfaces. Application by tyrolean box/ spray gun @ 2-5mm.	50 kg bags	430 m <sup>2</sup> @ 2mm thickness
	<b>Bonding Coat SP15</b>	Bonding coat for rendering on impermeable/non absorbing surfaces (EPS/XPS etc.). Application by tyrolean box/ spray gun @ 5-6mm.	50 kg bags	430 m <sup>2</sup> @ 2mm thickness
Cement Renders / Plasters	<b>Cement Plaster SP20</b>	Render/plaster for internal/external concrete block walls. Application by spray machine/manual @ 10-20mm.	50 kg bags	42 m <sup>2</sup> @ 15mm thickness
	<b>Cement Plaster SP22</b>	Render/plaster for internal/external AAC/concrete block walls. Application by spray machine/manual @ 10-20mm.	50 kg bags	42 m <sup>2</sup> @ 15mm thickness
	<b>Cement Plaster SP23</b>	Render/plaster for internal/external concrete block walls where high strength (>10 MPa) is required. Application by spray machine/manual @ 10-20mm.	50 kg bags	40 m <sup>2</sup> @ 15mm thickness
	<b>Cement Plaster SP24</b>	Render/plaster for high strength (> 15 MPa) requirements. Application by spray machine/manual @ 15-50mm.	50 kg bags	38 m <sup>2</sup> @ 15mm thickness
	<b>Cement Plaster SP25</b>	Fine thin coat plaster for ceilings and rough cement plaster surfaces. Application by spray machine/manual @ 4-6mm.	40 kg bags	162 m <sup>2</sup> @ 4mm thickness
	<b>Cement Plaster SP26</b>	Fine thin coat plaster for direct application on concrete surfaces. Application by spray machine/manual @ 3-8mm.	40 kg bags	152 m <sup>2</sup> @ 4mm thickness
Gypsum Plasters	<b>Gypsum Plaster SP30</b>	Standard gypsum plaster for internal AAC/concrete block walls. Application by spray machine/manual @ 10-20mm.	25 kg bags	58 m <sup>2</sup> @ 12mm thickness
	<b>Gypsum Plaster SP32</b>	Fine thin coat gypsum plaster for ceilings and rough cement plaster surfaces. Application by spray machine/manual @ 4-6mm.	25 kg bags	208 m <sup>2</sup> @ 4mm thickness
	<b>Gypsum Plaster SP34</b>	Fine thin coat gypsum plaster for direct application on concrete surfaces. Application by spray machine/manual @ 4-6mm.	25 kg bags	208 m <sup>2</sup> @ 4mm thickness

## Product list

Product category/name/code		Field of application	Packing	Approx. coverage [per tonne]
Masonry Mortars	<b>Masonry Mortar SP40</b>	Block laying mortar for concrete block works. Mixing by screw machine/manual.	50 kg bags	37 m <sup>2</sup> @ 10mm thickness (40x20x20cm block)
	<b>Adhesive Mortar SP42</b>	Block laying adhesive mortar for AAC block works. Mixing by screw machine/manual.	40 kg bags	108 m <sup>2</sup> @ 5mm thickness (60x25x20cm block)
	<b>Adhesive Mortar SP44</b>	Polymer modified block laying adhesive mortar for AAC block works. Mixing by screw machine/manual.	40 kg bags	108 m <sup>2</sup> @ 5mm thickness (60x25x20cm block)
Tile Adhesives	<b>Tile Adhesive SP50</b>	Economical grade Tile adhesive for ceramic/porcelain tiles on internal /external areas. Mixing by screw machine/manual.	25 kg bags	Yield 635 L/tonne
	<b>Tile Adhesive SP52</b>	High grade Tile adhesive for ceramic/porcelain tiles on internal /external areas. Mixing by screw machine/manual.	25 kg bags	Yield 685 L/tonne
	<b>Tile Adhesive SP54</b>	Flexible grade Tile adhesive for ceramic/porcelain/glass tiles on internal/ external areas. Mixing by screw machine/manual.	25 kg bags	Yield 685 L/tonne
Floor Screeds	<b>Floor Screed (15MPa - 40MPa) SP60</b>	Bonded/unbonded/floating leveling screed for floors. Mixing by machine/manual. Strength grade 15MPa-40MPa.	50 kg bags	Yield 530 L/tonne
Repair Mortars	<b>Repair Mortar SP70</b>	Fine repair mortar for concrete surfaces. Mixing by screw machine/manual.	40 kg bags	Yield 620 L/tonne
	<b>Repair Mortar SP75</b>	Fine repair mortar for plaster shrinkage cracks. Mixing by manual.	40 kg bags	Yield 650 L/tonne
Non-shrink Grouts	<b>Non-shrink Grout SP80</b>	Non-shrink grouting mortar for medium strength (40MPa) anchoring applications. Mixing by screw machine/manual.	50 kg bags	Yield 510 L/tonne
	<b>Non-shrink Grout SP82</b>	Non-shrink grouting mortar for high strength (70MPa) anchoring applications. Mixing by screw machine/manual.	50 kg bags	Yield 510 L/ton
Insulation Mortars	<b>Thermo Render SP90</b>	Thermal insulation render for external walls (Thermal conductivity value $\lambda = 0.075 \text{ W/m.K}$ ) Application by spray machine/manual @ 20-60mm.	20 kg bags	87 m <sup>2</sup> @ 20mm thickness
	<b>Thermo Adhesive SP92</b>	Adhesive/reinforcing layer for EPS/XPS thermal insulation sheets. Mixing by screw machine/manual.	40 kg bags	200 m <sup>2</sup> @ 3mm thickness

# Spray Plaster







- الطبقة الأولى
- بلاستر داخلي/ بلاستر خارجي
- بلاستر ملون
- بلاستر مزخرف
- بلاستر جبسي
- مونة الطابوق
- لاصق البلاط
- حشو فراغات البلاط
- مونة عازلة



## SCHNELL PUTZ W.L.L

SCHNELL PUTZ W.L.L

P.O.Box. 22035, Kingdom of Bahrain

Tel: (+973) 77 15 8228

Fax: (+973) 77 10 0347

E-mail: info@schnellputz.com

Website: www.schnellputz.com

شنيل بوتز ذ.م.م

ص.ب ٢٢٠٣٥ مملكة البحرين

تلفون : ٧٧ ١٥ ٨٢٢٨ ( +٩٧٣ )

فاكس : ٧٧ ١٠ ٠٣٤٧ ( +٩٧٣ )

البريد الإلكتروني : info@schnellputz.com

موقع : www.schnellputz.com